

Technical Service Report



Testing Laboratory:

Momentum Technologies Laboratories, Inc.
1507 Boettler Rd. Uniontown OH 44685 Ph: 330-595-4293 Fax: 330-595-4142

Customer:

Innovative Waterproofing Solutions
Nikolis D'Annunzio
48315 Gratiot Ave.
Chesterfield MI 48051

Project #:

AX22H9A

Quote #:

2019-265

Date of Report:

Friday, December 6, 2019

PO#:

1009

Abstract:

Analysis of one (1) product in accordance with ASTM E2178 Standard Test Method for Air Permeance of Building Materials.

MTI#	Description of Material	Receiving Date
MTI-182517	Six (6)- 1m x 1m IWS Water Proof cured film samples assembled by customer	8/22/2019



Results and Conclusion

Laboratory Conditions

Average Lab Barometric Pressure, kPa	97.20
Average Air Flow Temperature, °C	25.50
Density of Air Through Flow Meter, kg/m ³	1.20

Conclusion: These laboratory conditions are used to convert all flow readings to STP in accordance with ASTM E 283 Section 12.1.

Test setup


The above specimens were attached as a free film to a wooden frame for support with a 1m x 1m opening and an embedded screen with an air permeance greater than the film being tested. The testing apparatus was then attached to the wooden frame and tested per ASTM E 2178 section 8. **These specimens were not applied to any substrate; they were tested as a free film.**

Results and Conclusion

	ΔP , Pa					
	25	50	75	100	150	300
Std. Dev.	0.00058	0.00064	0.00065	0.00063	0.00066	0.00058
Average Flow, L/(s*m ²)	0.00069	0.00091	0.00111	0.00128	0.00179	0.00350
Average Flow, cfm/ft ²	0.00014	0.00018	0.00022	0.00025	0.00035	0.00069
Upper Limit @ 95% Confidence	0.00140	0.00171	0.00191	0.00207	0.00261	0.00422
Lower Limit @ 95% Confidence	0.00000	0.00011	0.00030	0.00050	0.00097	0.00277
Requirement, L/(s*m ²), cfm/ft ² , Max	N/A	N/A	0.02 0.004	N/A	N/A	N/A
Conclusion	N/A	N/A	Pass	N/A	N/A	N/A
*Material Permeance, P	0.000028	0.000018	0.000015	0.000013	0.000012	0.000012

*P= $Q/(\Delta P * A)$, Where Q= Flow Rate, ΔP = Pressure Differential, A= Area

Results and Conclusion



Results and Conclusion

Conclusion:

The results above indicate the flow through the specimens with a unit of measurement of L/(s*m2) in accordance with ASTM E 2178 Section 8. The permeance is calculated in accordance with ASTM E 2178 Section 10.3. The log/log graph indicates an excellent correlation between flow and air pressure differential with an r^2 value greater than 0.99, conforming with ASTM E 2178 Section 11.1.3.1.

Tested By:

Stacey Weister

Construction Laboratory Supervisor

Reviewed By:

Rodney Armstrong

Managing Director

Revision Log

Revision #	Date	Revision
1	12/6/2019	Change Company Name
0	12/6/2019	Original

The information presented in this publication is based upon the research of Momentum Technologies Laboratories, Inc. (MT Labs) and is to the best of its knowledge accurate. However, no guarantee of its accuracy can be made since MT Labs has no control over the conditions under which its products may be used by others. MT Labs assumes no liability for its use, or the failure of products described herein. MT Labs MAKES NO WARRANTIES EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS, PATENT INFRINGEMENT, OR OTHERWISE. MT Labs SHALL NOT BE LIABLE FOR SPECIAL, INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES. No statement contained herein shall be construed as a recommendation or inducement to infringe existing patents or as an endorsement of products of specific manufacturers. ALL TEST REPORTS SHALL NOT BE REPRODUCED, EXCEPT IN FULL WITHOUT THE WRITTEN APPROVAL OF MT Labs

